

# SLING SAILING

## Technical sheet



| CHARACTERISTICS | VALUES |      | UNITS | STANDARDS |
|-----------------|--------|------|-------|-----------|
|                 | WARP   | WEFT |       |           |

### GENERAL CHARACTERISTICS

|                  |                                                    |  |      |            |
|------------------|----------------------------------------------------|--|------|------------|
| Composition      | 35 % Sunbrella Acrylic 17.8 % Polyester 47.2 % PVC |  |      |            |
| Backing / Finish | Non PFAS                                           |  |      |            |
| Weave            | Dobby                                              |  |      | ISO 7211-1 |
| Weight           | 580                                                |  | g/m² | ISO 3801   |
| Width            | 137                                                |  | cm   | EN 1773    |
| Roll length      | 40                                                 |  | ml   |            |

### FABRIC RESISTANCE

|                       |     |     |         |             |
|-----------------------|-----|-----|---------|-------------|
| Tensile strength      | 200 | 300 | daN/5cm | ISO 13934-1 |
| Elongation at break   | 24  | 24  | %       | ISO 13934-1 |
| Seam slippage (180 N) | <2  | <2  | mm      | ISO 13936-2 |
| Stitching strength    | 190 | 305 | N       | ISO 13935-2 |

### COLOUR-FASTNESS

|                                      |     |  |           |             |
|--------------------------------------|-----|--|-----------|-------------|
| Colour fastness UV - outdoor - 1000h | 4/5 |  | Class / 5 | ISO 105 B04 |
| Colour fastness UV - indoor          | 8   |  | Class / 8 | ISO 105 B02 |
| Colour fastness under dry friction   | 5   |  | Class / 5 | ISO 105X12  |
| Colour fastness under wet friction   | 5   |  | Class / 5 | ISO 105X12  |
| Colour fastness 30°C washing         | 5   |  | Class / 5 | ISO 105 C06 |

### FIRE RESISTANCE

|                                                 |      |
|-------------------------------------------------|------|
| California Technical Bulletin 117-203 Section 1 | Pass |
| NFPA 260 Classe I                               | Pass |
| NF EN 1021-1                                    | Pass |
| BS 5852 Part 1 Source 0                         | Pass |

### USES

|                  |                   |       |  |
|------------------|-------------------|-------|--|
| Guarantee        | 5                 | years |  |
| Recommended Uses | Seating, Cushions |       |  |

### CARE



This product's values may vary with a tolerance of  $\pm 5\%$

**Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration**  
10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France  
Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - [www.dickson-constant.com/en/UK](http://www.dickson-constant.com/en/UK)

