

SLING AUGUSTINE

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	11 % Sunbrella Acrylic 25 % Polyester 64 % PVC			
Backing / Finish	Non PFAS			
Weave	Dobby			ISO 7211-1
Weight	505		g/m²	ISO 3801
Width	137		cm	EN 1773
Roll length	40		ml	

FABRIC RESISTANCE

Tensile strength	205	255	daN/5cm	ISO 13934-1
Elongation at break	29	30	%	ISO 13934-1
Seam slippage (180 N)	<2	<2	mm	ISO 13936-2
Stitching strength	500	542	N	ISO 13935-2

COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4/5		Class / 5	ISO 105 B04
Colour fastness UV - indoor	8		Class / 8	ISO 105 B02
Colour fastness under dry friction	5		Class / 5	ISO 105X12
Colour fastness under wet friction	5		Class / 5	ISO 105X12
Colour fastness 30°C washing	5		Class / 5	ISO 105 C06

FIRE RESISTANCE

California Technical Bulletin 117-203 Section 1	Pass
NFPA 260 Classe I	Pass
NF EN 1021-1	Pass
BS 5852 Part 1 Source 0	Pass

USES

Guarantee	5	years	
Recommended Uses	Seating, Cushions,		

CARE



This product's values may vary with a tolerance of $\pm 5\%$

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration
10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France
Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK

