

CLIFF WATERPROOF

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	68% Sunbrella Acrylic 32% PU			
Backing / Finish	Non PFAS - Water-repellent & Stain-proof			
Weave	CANVAS			ISO 7211-1
Weight	308		g/m²	ISO 3801
Width	138		cm	EN 1773
Roll length	50		ml	

FABRIC RESISTANCE

Tensile strength	94	74	daN/5cm	ISO 13934-1
Elongation at break	48.2	42	%	ISO 13934-1
Pilling	5		Class / 5	ISO 12945-2
Schmerber	> 1500		mm	ISO 811
Spray test	5		Class / 5	ISO 4920
Seam slippage (180 N)	< 3	< 3	mm	ISO 13936-2
Stitching strength	560	495	N	ISO 13935-2
Stability on 30 deg. C washing	+/- 1%	+/- 1%	%	ISO 5077

COLOUR-FASTNESS

Colour fastness UV - outdoor - 1000h	4-5		Class / 5	ISO 105 B04
Colour fastness UV - indoor	8		Class / 8	ISO 105 B02
Colour fastness under dry friction	5		Class / 5	ISO 105X12
Colour fastness under wet friction	5		Class / 5	ISO 105X12
Colour fastness 30°C washing	5		Class / 5	ISO 105 C06

USES

Guarantee	5	years	
Recommended Uses	Seating, Cushions		

CARE



This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration
10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France
Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK

